



Dewpoint Art. Nr. 5020-0561 31.05.2006

Combination instrument for temperature, humidity and dewpoint

## Pocket Dewpoint Pro



- **Very fast capacity humidity sensor from the switzerland**
- **Indicates dewpoint and wetbulb**
- **1- second measuring interval**
- **MAX-MIN-HOLD-Function**
- **C/F-switchable**

### Applications

Pocket size thermohygrometer with a lot of features, perfect for measuring ambient conditions: HVAC, food storage, buildings, offices, production plants. Easy to use: For detecting critical temperature-humidity environments, e.g.: mould in living quarters.

- § Building industry
- § HVAC
- § Education
- § Laboratory
- § Food (process & storage)

### Technical data

Incl. stand

#### Temperature

Measuring range -40..+70°C  
 Display resolution 0,1°C  
 Accuracy  $\pm 0,5^\circ\text{C}$

#### Humidity

Measuring range 0..99%rF  
 Display resolution 0,1%  
 Accuracy  $\pm 3\%$ (20..80%), remaining range  $\pm 4\%$

Working temperature -40..70°C  
 Battery life time Typical 200 hours by continuously use  
 Battery 1 x CR1225  
 Dimensions 160 x 50 x 45 mm  
 Weight 100gr. (incl. packaging)

Functions: Max/Min/Hold-Function, dewpoint, wetbulb, calibration certificate as an option  
 C/F-switchable