

Dewpoint Art. Nr. 5020-0560 06.04.2005

Combination instrument for temperature, humidity and dewpoint**Dewpoint Pro**

- **Very fast capacity humidity sensor from the switzerland**
- **Indicates dewpoint and wetbulb**
- **1- second measuring interval**
- **MAX-MIN-HOLD-Function**
- **C/F-switchable**
- **Switchable Auto-off-function**

Applications

Compact thermohygrometer with a lot of features, perfect for measuring ambient conditions: HVAC, food storage, buildings, offices, production plants. Easy to use: For detecting critical temperature-humidity environments, e.g.: mould in living quarters.

- § Building industry
- § HVAC
- § Education
- § Laboratory
- § Food (process & storage)



Incl. stand

Technical data**Temperature**

Measuring range -40..+70°C
Display resolution 0,1°C
Accuracy $\pm 0,5^\circ\text{C}$

Humidity

Measuring range 0..99%rF
Display resolution 0,1%
Accuracy $\pm 3\%$ (20..80%) remaining range $\pm 4\%$

Working temperature -40..70°C
Battery life time Typical 1000 hours by continuously use
Battery 2 x 1,5 Volt AAA size
Dimensions 170 x 50 x 17 mm
Weight 100gr. (incl. packaging)

Functions: Max/Min/Hold-Function, dewpoint, wetbulb, calibration certificate as an option
C/F-switchable